WS4949 Two-Button Wireless Key



Product Features:

- Cost effective
- ► Two-button, three-channel wireless key
- ► Activation via two large, scratch-resistant buttons
- Attractive, compact design
- ► Full three-second delay on panic function
- ► Integrated LED to indicate signal transmission
- Reliable 433MHz technology
- Long-life lithium batteries included
- FCC/IC approved



WS4949

The WS4949 two-button wireless key adds wireless convenience and value to any DSC security system by providing users with a competitively priced wireless solution that includes a number of features and benefits. The WS4949 provides users with a sense of control over their security system and the added confidence that comes with portable personal protection within the home. Compact and user-friendly, the WS4949 features two scratch-resistant buttons that when activated perform either away arming or disarm functions. When the two buttons are pressed simultaneously the panic function is activated.

False Alarm Reduction

False alarm reduction has resulted in the introduction of activation delays that require users to press and hold a button for a period of time before its function is initiated. To activate the away arming/disarm functions of the WS4949, press and hold the appropriate button until the one-second activation delay expires. The WS4949 incorporates a full, three-second activation delay on its panic function to help reduce false alarms. To activate it, both buttons need to be pressed simultaneously.

Visual Confirmation

A red LED indicator, located between the two buttons on the WS4949, flashes to indicate that a transmission has been sent to the security system.

Value Added

Distributed by

The WS4949 uses reliable 433MHz wireless technology, long-life lithium batteries and is compatible with all of DSC's current wireless receivers.

Ordering Information	:
WS4949	2-Button Wireless Kev



Compatibility

The WS4949 is compatible with the following receivers:

MAXSYS® Wireless Receiver PC4164-433

PowerSeries™ Wireless Receiver Zone Expansion Module PC5132-433

Wireless Receiver RF5108-433

Fixed-Message LCD Keypad with Integrated Wireless Receiver RF5501-433

Envoy™ LCD Self-Contained Wireless Security System NT9005

Specifications

Dimensions	. 2 1/4" x1 1/4" x 7/16"
	(57mm x 32mm x 13mm)
Weight	. 0.6oz
	(18g)
Operating Environment	
	(0° to 49°C)
Relative Humidity	. 5% to 93%